



Shown to depict scale

Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Valve Internal Hex Size	3/16 in.
Seal kit - Cartridge	Buna: 990382007
Seal kit - Cartridge	EPDM: 990382014
Seal kit - Cartridge	Viton: 990382006

**CONFIGURATION OPTIONS**

Model Code Example: **CXZAXCN**

CONTROL	(X) CRACKING PRESSURE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>C</b> 30 psi (2 bar)	<b>N</b> Buna-N	Standard Material/Coating
	<b>A</b> 4 psi (0,3 bar)	<b>E</b> EPDM	/AP Stainless Steel, Passivated
	<b>B</b> 15 psi (1 bar)	<b>V</b> Viton	/LH Mild Steel, Zinc-Nickel